

AIRBORNE

by anandic

NXTGEN

TRANSPORT INCUBATOR

THE NEXT GENERATION OF NEONATAL TRANSPORT



AIR



GROUND

Easy clinical access to the patient
Touch screen user interface
Safe and secure air or ground transport
Compact and customizable options

International BIOMEDICAL®

Standard Features:

Infant Chamber

- Sizes: Extra Large (XL) or Low Profile (LP)
- Main Access Door: 21.6 x 57 cm
- 6 Hand Ports: 13.9 x 16.5 cm (Oval Shape)
- 8 Access Ports for IV/Respiratory Tubing

Dynamic Patient Tray

- Mattress: 31.8 x 61.0 x 2.5 cm
- Maximum Patient Weight: 10 kg
- Mattress to Chamber Height: 24.1 cm (XL)
- Mattress to Chamber Height: 19.0 cm (LP)
- Quick Release with No Tools
- Vibration Isolation System

Touch Screen User Interface

- Touch Screen: 17.8 cm (diagonal)
- 800 x 480 pixels
- Data Trending & Output
- Stop Watch
- Countdown Timer
- Screen Lock
- Screen Brightness Adjustment: 5 (20%)
- Event Log
- Languages: English, German, Spanish, French, Swedish, Italian
- Self-test function performed at power on & continuously during operation

Thermal Performance

- Thermal Control Modes: Servo & Manual
- Air Temp Set Point Range: 17.0 – 38.9°C
- Servo Temp Set Point Range: 33.0 – 37.5°C
- Temperature Display Resolution: 0.1°C
- Temperature Accuracy: ± 1.0°C
- Warm-up Time: 12 min (LP) & 16 min (XL)
- Airflow Filtration: < 5 microns
- Carbon Dioxide Concentration: < 0.5%
- Temperature Display Update Period: 1 sec
- Audible Noise Level: < 60 dBA
- Air Velocity Across the Mattress: < 0.35 m/s
- Temperature Probe Accuracy: ± 1.0°C
- Microprocessor controlled system

LED Observation Light

- Intensity: >500 Lux
- Intensity Increments: 5 (20%)
- Power: 10 watts

Alarms & Indicators

- Adjustable Alarm Intensity: 65 dBA Max - 50 dBA Min (@3m)
- Color Coded Visual Alarms
- Alarm Messages Communicated in Plain Text
- Alarms: Chamber Temperature HI/LO (Manual Mode), Patient Temperature HI/LO (Servo Mode), Airflow Blocked, AC Disconnect, Power Fail, Airflow Fan Fail, Low Battery, System Fail, Air Temp Sensor, Speaker Fail*

Europe

International Biomedical AG

Glütschbachstrasse 100, CH-3661 Uetendorf, Switzerland
T. +41.33.345.66.00
welcome@int-bio.ch

Physical Specifications:

- Dimensions
 - Length: 76.2 cm
 - Width: 42.4 cm
 - Height (XL Chamber): 60.9 cm
 - Height (LP Chamber): 55.9 cm
- Weight: 38.0 kg without handles or accessories

Electrical Specifications:

- AC Power (Incubator): 100-240 VAC, 50/60 Hz, 3 A Max
- Total Power: XX VA (Max)
- 8 AC Accessory Outlets: 7 A Max (Total) at input voltage
- External DC Power Input: 12-28 V, 15 A Max
- External DC Power Output: 3 A, at input voltage
- Battery Chemistry: Sealed Lead/Acid (SLA) or Lithium Iron Phosphate (LiFePO4) (Optional)
 - LiFePO4 Battery Voltage: 12 V
 - LiFePO4 Battery Capacity: 32 Ah
 - LiFePO4 Battery Life: 1000 cycles
 - LiFePO4 Battery Weight: 5 kg
 - SLA Battery Voltage: 12 V
 - SLA Battery Capacity: 26 Ah
 - SLA Battery Life: Approx. 200 cycles
 - SLA Battery Weight: 10 kg
 - Nominal Battery Operation Time
 - LiFePO4 Battery: 5.0 hr. at 37°C
 - SLA Battery: 4.0 hr. at 37°C
 - Nominal Battery Recharge (90%) Time: 4.5 hr. on A/C Power, Unit Off

Operational Specifications:

- Temperature: 15 - 40°C
- Humidity: 5% - 95% non-condensing
- Pressure: 70 kPa – 110 kPa

Storage Specifications:

- Temperature: -25 - 60°C
- Humidity: 5% - 95% non-condensing
- Pressure: 50 kPa – 110 kPa

Standards & Approvals:

- 60601-1
- 60601-1-2
- 60601-1-6
- 60601-1-8
- 60601-1-12
- 60601-2-20
- 60601-2-35
- 60601-2-50
- 10079-1
- 80601-2-55
- 80601-2-61
- RTCA DO-160
- Class II / Internally Powered, according to the type of protection against electrical shock
- Incubator & its applied parts are Type BF Equipment
- IP 33

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. 512.873.0033 F. 512.873.9090
sales@int-bio.com

Optional Features:

Heated Mattress

- Heated Mattress Size: 31.8 x 61.0 x 2.5 cm
- Power: 22 watts Max, 40°C Max

Phototherapy

- Light Spectrum Range: 450 – 465 nm
- Maximum Irradiance:
 - LP Chamber: 35 µW/cm2/nm
 - XL Chamber: 22 µW/cm2/nm
- Effective Irradiated Area:
 - LP Chamber: 12.3 x 9.2 inch ellipse
 - XL Chamber: 15.1 x 10.8 inch ellipse
- Power: 10 watts Max

Pulse Oximetry

- Technology: Masimo SET or Nellcor Oximax
- Measurement Range:
 - SpO2: 1 – 100%
 - Pulse Rate: 25-239 bpm
- Resolution:
 - SpO2: 1%
 - Pulse Rate: 1 bpm
- Masimo SET Sensor Accuracy
 - SpO2 70 - 100%: ± 3%
 - SpO2 0 - 69%: unspecified
 - Pulse Rate: ±3 bpm (no motion), ±5 bpm (motion)
- Nellcor Sensor Accuracy
 - SpO2 70 - 100%: ± 2%
 - Pulse Rate: ±3 bpm

Ambient Oxygen Monitor

- Measurement Range: 10.0 – 100% O2
- Resolution: 0.1%
- Accuracy: ± 4.0%
- Stability: < 2% drift over 8 hours
- Response Time: < 16 sec for 90% response

Suction

- Vacuum Pressure Range: 10-150 mmHg
- Vacuum Max Pressure: 150 mmHg
- Flow rate at vacuum inlet: 10 LPM
- Vacuum Pressure Accuracy: ± 5 mmHg
- Audible Noise Level: < 60 dBA
- Power: 20 watts Max

Airway Management

- Intelligent, Automatic Gas Switching Manifold
 - Air/Oxygen Inputs (External Gas)
 - Air/Oxygen Inputs (Cylinder Gas)
 - Options for DISS or NIST
- 1 or 2 sets of Air/Oxygen Outputs
- Air & Oxygen Blender: 21 – 100% FiO2
- Mixed Gas Flow Meter: 0 – 15 L/min

int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.